

BSD 00, 000, 000 0000

Abstract

00000000 00000000 0000 "00000000 00000000" 0000 000 00000000 00 0000 0000 0000 000000 0000000000'0
00000000 000000000 00000000 0000 0000000000 000000000 00000000 00000000 00000000 0000 00 00000000 00000000
000000000000 0000 000000 00000000 00.0% 00000000000 00000000 0000 00 0000000000 00 00.0% 00000000000 00000000
00 BSD 000000000 00000000 0000000000; 0000000000 00000000 0000000000000000 0000000, 00000, [Yahoo!](#) BSD 00000000
00000000 0000 000000 00000000 0000000000 FTP 00000000 [ftp.cdrom.com](#) BSD 00000000 0000 0000000000 000000 0.0
000000000 0000 0000 00000000 0000 00000000 BSD'0 000000 00 00000000 0000, 0000 0000 00000000 0000 BSD 0000
0000000000 00000000 000000 000000000

BSD'0 000000000 00000000 000000 00 0000 000000 0000 ? 00 0000000000 0000 00000 0000 00000 0000000000000000 00 00000000
000000000000

00 0000000000 BSD 0 000000000000 00 0000000000000000 000000 00000000 0000 00000

Table of Contents

- 1. BSD 00 ? 1
- 2. 000 0000000!!! 0000 0000 00 ? 2
- 3. BSD 000 000000000 00 ? 3
- 4. BSD 0000 0000000000 3

1. BSD 00 ?

BSD 0000 00 *Berkley Software Distribution* 0 000000000000 BSD 0000 0000000000000000 0000000000000000,
00000000 0000 0000000000 000000000000 00000000 0000 AT&T'0 000000000000 00000000 0000000000 0000 00000000
0000 00 0000000000 0000 00000000 4.4BSD-Lite 0000 00000000 00 0000000000 00000000 0000 0000 00000000 0000000000
0000000000 0000000000 0000 00000000 00 00000000000000 0000 00000 0000000000 00000000000 00000000 00000000
0000, 0000 000000 00000000000000 00 00000 (GNU) 00000000000 0000000000000000 0000 BSD 0000000000 0000000000 0000000000
000000000 00 0

BSD 00000000

0000 000000000 0000000000 000000 0000 0 000000 000000 0000 0000 00000000 00000000 000000 0000000000 0000000000 000000
000000 00000000 000000000000 00000000000 00000

00000000 00000000 00, 00000000000 000000000 00000 00000 000000000000 0000000, 00000000 BSD 00000000000 00000000
00000000 0000 00000 000000000000 000000 0000000000000000 0000 00000000000 000000000000 0000

C 0000000000

0000 00 0000000000 00000000000 API 0000000000 0000 0000000000

BSD C 000000000000 0000000000 0000000000 0000000000 0000, 000000 (GNU) 00000000000000 0000 00000 0000

4. 通常情況下，CVS 是 BSD 的代碼倉庫。但對於某些 BSD 發行版，CVS 代碼倉庫可能位於其他位置。請參閱該發行版的文檔以獲取更多信息。

對於 BSD 發行版，通常情況下，代碼倉庫位於以下位置：
• 對於 FreeBSD，代碼倉庫位於 `http://svn.freebsd.org/`。
• 對於 NetBSD，代碼倉庫位於 `http://cvs.NetBSD.org/`。
• 對於 OpenBSD，代碼倉庫位於 `http://cvs.openbsd.org/`。

1. 通常情況下，CVS 是 BSD 的代碼倉庫。但對於某些 BSD 發行版，CVS 代碼倉庫可能位於其他位置。請參閱該發行版的文檔以獲取更多信息。
2. 通常情況下，CVS 是 BSD 的代碼倉庫。但對於某些 BSD 發行版，CVS 代碼倉庫可能位於其他位置。請參閱該發行版的文檔以獲取更多信息。
3. RELEASE 通常情況下，CVS 是 BSD 的代碼倉庫。但對於某些 BSD 發行版，CVS 代碼倉庫可能位於其他位置。請參閱該發行版的文檔以獲取更多信息。

4.3. BSD 的代碼倉庫

通常情況下，CVS 是 BSD 的代碼倉庫。但對於某些 BSD 發行版，CVS 代碼倉庫可能位於其他位置。請參閱該發行版的文檔以獲取更多信息。

通常情況下，CVS 是 BSD 的代碼倉庫。但對於某些 BSD 發行版，CVS 代碼倉庫可能位於其他位置。請參閱該發行版的文檔以獲取更多信息。

- FreeBSD 的代碼倉庫位於 `http://svn.freebsd.org/`。
- NetBSD 的代碼倉庫位於 `http://cvs.NetBSD.org/`。
- OpenBSD 的代碼倉庫位於 `http://cvs.openbsd.org/`。

BSD license and other licenses

BSD license and other licenses are used in BSD/OS and Mac OS X

- 4.4 BSD license and other licenses are used in BSD/OS and Mac OS X, and FreeBSD's BSD/OS license is also used
- BSD license and other licenses are used in Mac OS X and FreeBSD's BSD license is also used

4.4. BSD and GNU licenses

BSD license and GNU General Public License (GPL) are used in BSD/OS and Mac OS X. BSD license is a permissive license, while GPL is a copyleft license. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to the user.

4.5. BSD license and other licenses

BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while other licenses like GPL are more restrictive. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to the user.

BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while other licenses like GPL are more restrictive. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to the user.

4.6. BSD license and other licenses

BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while other licenses like GPL are more restrictive. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to the user.

BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while other licenses like GPL are more restrictive. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to the user.

- BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while other licenses like GPL are more restrictive. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to the user.
- BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while other licenses like GPL are more restrictive. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to the user.
- BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while other licenses like GPL are more restrictive. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to the user.
- BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while other licenses like GPL are more restrictive. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to the user.

- 00000000000 00000000 BSD'00 0000000 000000 0000 00000000 000000 0000 00 0000 0000000000 0000000000 0000000000 00000000 00000000 BSD'0 00000000000 00000000 00000000000 0000000 0000000

4.7. BSD 000000000000 000000 0 0000000000000

BSDi 00000000 BSD/OS 00000000000 00000 00000 00000000 0000000000 00000 FreeBSD 000000000 00000 00000000 0000000000

00000000 FreeBSD, NetBSD 0 OpenBSD'0 00000000000 0000000000 000000 000000 00000 0000000000000 0000000000 0000000000000 00000 00000 0000000 00000